

# Cincinnati Industrial Auctioneers



## Moving Liquidation Sale of Pearl Equipment Company

Including Presses by Verson and Komatsu, Feed Equipment, Press Brakes, Shears, Rollformers, Tube Mills, Lathes, Grinders, Parts Washers & more!

4717 Centennial Blvd.  
Nashville  
Tennessee  
37209  
United States

Started Jan 22, 2020 10am CT (4pm GMT)

Lot	Description
1	1,000 LB. LITTELL NO. 10 AUTOMATIC CENTERING REEL; STOCK NO. 17013A ** DELTA, OHIO ** ** D&D INDUSTRIES HAS QUOTED \$50.00 FOR SIMPLE LIFT & LOAD **
2	DEXTER 4-STAND RING ROLLING ROLL FORMER; S/N R-3111, 2.125" DIA. SHAFTS, 5" ROLL SPACE, 9" CENTERS; STOCK NO. 17013C ** DELTA, OHIO ** ** D&D INDUSTRIES HAS QUOTED \$400.00 FOR SIMPLE LIFT & LOAD **
3	40 TON ROUSSELLE MODEL 40H HORN PRESS; S/N 22039, 6" STROKE, 26" LRX, 12" FRONT TO BACK BEND AREA, 45 SPM; STOCK NO. 17013D **MONCLOVA, OHIO ** D&D INDUSTRIES HAS QUOTED \$400.00 FOR SIMPLE LIFT & LOAD **
4	{ Choice of lots: 4 } 35 TON NIAGARA MODEL AMB-35 ADJUSTABLE BEND HORN PRESSES; S/N 49359, 24" LEFT TO RIGHT X 16" FRONT TO BACK, 5" STROKE; STOCK NO. 17013E ** MONCLOVA, OHIO **D&D INDUSTRIES HAS QUOTED \$400.00 FOR SIMPLE LIFT & LOAD **
5	{ Choice of lots: 5 } 35 TON NIAGARA MODEL AMB-35 ADJUSTABLE BEND HORN PRESSES; S/N 49362, 24" LEFT TO RIGHT X 16" FRONT TO BACK, 5" STROKE; STOCK NO. 17013F ** MONCLOVA, OHIO **D&D INDUSTRIES HAS QUOTED \$400.00 FOR SIMPLE LIFT & LOAD **
6	{ Choice of lots: 6, 7 } 35 TON NIAGARA MODEL AMB-35 ADJUSTABLE BEND HORN PRESSES; S/N 49363, 24" LEFT TO RIGHT X 16" FRONT TO BACK, 5" STROKE; STOCK NO. 17013Q ** MONCLOVA, OHIO **D&D INDUSTRIES HAS QUOTED \$400.00 FOR SIMPLE LIFT & LOAD **
7	{ Choice of lots: 6, 7 } 35 TON NIAGARA MODEL AMB-35 ADJUSTABLE BEND HORN PRESSES; S/N 51901, 24" LEFT TO RIGHT X 16" FRONT TO BACK, 5" STROKE; STOCK NO. 17013N ** MONCLOVA, OHIO **D&D INDUSTRIES HAS QUOTED \$400.00 FOR SIMPLE LIFT & LOAD **
8	150 TON NIAGARA MODEL E-150 OBI PRESS; S/N 52221, 10" STROKE, 27 SPM, 50" LEFT TO RIGHT X 30" FRONT TO BACK BEND AREA, 26" SHUT HEIGHT, 6" RAM ADJUSTABLE, AIR CLUTCH, COUNTER BALANCE (1984); STOCK NO. 17946 ** NASHVILLE, TENNESSEE ** PEARL EQUIPMENT COMPANY HAS QUOTED \$1,000.00 FOR SIMPLE LIFT &am ...[more]
9	90 TON NIAGARA MODEL E90 OBI BACK GEARED PRESS; S/N 52482, 39" LEFT TO RIGHT X 25" FRONT TO BACK BED, 9" STROKE, 46 SPM, 18" SHUT HEIGHT, 4.5" RAM ADJUST, AIR CLUTCH; STOCK NO. 17013G ** MONCLOVA, OHIO ** D&D INDUSTRIES HAS QUOTED \$700.00 FOR SIMPLE LIFT & LOAD **
10	90 TON NIAGARA MODEL E-90 OBI BACK GEARED PRESS; S/N 52536, STROKE 9", SHUT HEIGHT 18" SDAU, ADJSUTAMENT 4.5", BED AREA 39" LEFT TO RIGHT X 25" FRONT TO BACK, RAM AREA 27.5" LEFT TO RIGHT X 20" FRONT TO BACK X 2" HIGH, SPM 45, BOLSTER THICKNESS 2", CONTROL PALM BUTTON STATION, FLOOR STANDING, ELECT ...[more]

- 11 250 TON NIAGARA MODEL E250 GAP FRAME PRESS; S/N 51238, 58" LEFT TO RIGHT X 34" FRONT TO BACK BED, 12" STROKE, 27 SPM, 22" SHUT HEIGHT, 6" RAM ADJUSTABLE, AIR CUTCH, COUNTER BALANCE (1980); STOCK NO. 17950 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$1,200.00 FOR SIMPLE LIFT & ...[more]
- 
- 12 200 TON NIAGARA MODEL S2G-200-60-30 DOUBLE CRANK GAP FRAME PRESS; S/N 50783, 60" LEFT TO RIGHT X 30" FRONT TO BACK BED, 10" STROKE, 30 SPM, 24" SHUT HEIGHT, 6" RAM ADJUSTABLE, PALM BUTTON, AIR CLUTCH, COUNTER BALANCE, FLOOR STANDING; STOCK NO. 17949 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY ...[more]
- 
- 13 150 TON NIAGARA E-150 OBS SINGLE POINT GAP FRAME PRESS; S/N 50978, BED SIZE 50" X 30", RAM SLIDE AREA 34" X 24", T-SLOTTED BOLSTER 48" X 33" X 5" THICKNESS, BOLSTER 5", STROKE 6", MAX RATED CAPACITY .25 ABOVE BOTTOM STRIKE, SPM 35, SHUT HEIGHT 20.5", MOTORIZED ARI RAM ADJUSTMENT 6", FLOOR TO TOP O ...[more]
- 
- 14 27.5 TON KOMATSU MODEL OBS-25-3 SINGLE POINT GAP FRAME PRESS; S/N 11828, SPM 125, STROKE LENGTH 3.15", SHUT HEIGHT 7.87", ADJUSTMENT 1.97", RAM AREA 9.84" X 7.87", BED AREA 29.53" LEFT TO RIGHT X 11.81" FRONT TO BACK, BOLSTER THICKNESS 2.68", 3 HP (1989); STOCK NO. 17925 \*\* NASHVILLE, TENNESSEE \*\* ...[more]
- 
- 15 450 TON MODERN MODEL UNK 4-POST HYDRAULIC PRESS; S/N N/A, USED MODERN 450 TON 4-POST HYDRAULIC PRESS, CAPACITY 450 TON, BED SIZE 68" X 56", DAYLIGHT 31", DISTANCE BETWEEN POST 52" X 39", STROKE 24", 150 HP MOTOR; STOCK NO. 17963 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$1,000.0 ...[more]
- 
- 16 660 TON KOMATSU SERVO PRESS MODEL HF4-600 STRAIGHT SIDE DOUBLE CRANK PRESS; S/N 10001, 11.81" STROKE, 45.26" SHUT HEIGHT, 11.81" SLIDE ADJUSTMENT, 196-8" X 62.89" BED AND RAM, 84" WINDOWS, OVER DROP DISTANCE 150 MM, STOPPING TIME 470 MS, MAX STOPPING TIME 495 MS, 26,458 LB. ALLOWABLE UPPER DIE MASS ...[more]
- 
- 17 600 TON VERNON MODEL S2-600-120-72T STRAIGHT SIDE DOUBLE CRANK PRESS; S/N 24770, 120" LEFT TO RIGHT X 72" FRONT TO BACK BEND SIZE, 20 TO 40 VARIABLE SPM, 10" STROKE, 46" SHUT HEIGHT, 12" RAM ADJUSTMENT, 33-1/2" WINDOWS, LINK TONNAGE AND BRAKE MONITOR, AIR CLUTCH, AIR COUNTER BALANCE; STOCK NO. 1795 ...[more]
- 
- 17A 600 TON BROWN & BOGGS MODEL SS2-600-168-60E STRAIGHT SIDE DOUBLE CRANK PRESS; S/N 97114, 12" STROKE, 26" SHUT HEIGHT OVER BOLSTER, 12" ADJUSTMENT, 168" X 60" BED SIZE, 20 - 40 SPM, AIR CLUTCH, AIR BRAKE, AIR COUNTERBALANCES, OMNI LINK LCD CONTROL, TRABON LUBE SYSTEM, LIGHT CURTAINS, 53" WINDOWS ...[more]
- 
- 17B { Choice of lots: 17B, 17C } 330 TON AIDA MODEL PMX-L2-300(1) STRAIGHT SIDE DOUBLE CRANK PRESS; S/N 12903-0696, 5.90" STROKE, 3.93" POWER RAM ADJUSTMENT, 18.50 SHUT HEIGHT OVER BOLSTER, 50 -120 SPM, 72.84" X 34.65" RAM, 73.84" X 39.37" BED, T-SLOTTED RAM AND BOLSTER, 36.5" WIDE WINDOWS, AIR CLUTCH, ...[more]
- 
- 17C { Choice of lots: 17B, 17C } 330 TON AIDA MODEL PMX-L2-300(1) STRAIGHT SIDE DOUBLE CRANK PRESS; S/N 12903-0665, 5.90" STROKE, 3.93" POWER RAM ADJUSTMENT, 18.50 SHUT HEIGHT OVER BOLSTER, 50 -120 SPM, 72.84" X 34.65" RAM, 73.84" X 39.37" BED, T-SLOTTED RAM AND BOLSTER, 36.5" WIDE WINDOWS, AIR CLUTCH, ...[more]
- 
- 18 30 TON L&J MODEL PM2-30-24-18 SSDC HIGH SPEED PRESS; S/N PM2-107A, CAPACITY 30 TON, SPM 60-300 VS, STROKE 2", ADJUSTMENT 2", SHUT HEIGHT, SDAU 12-1/2", BED AREA 24" LEFT TO RIGHT X 18" FRONT TO BACK, RAM AREA 24" LEFT TO RIGHT X 18" FRONT TO BACK, RECIRCULATING OIL LUBRICATION, ISOLATOR PADS; S ...[more]
- 
- 19 11,000 LB. X 39" X .177 SONORUKA SERVO FEED LINE; S/N 4533-4550, COIL WEIGHT 5,000 KG - 11,023 LB., COIL OD 800-1500 MM - 31.49" - 59.05", COIL ID 508-610MM - 20"-24.01", SPEED 25 M/ MIN - 984" IPM, POWER EXPANSION, TRAVELING COIL CAR, TWO ARM TURNSTYLE, PEELER TABLE, POWERED THREADING DRIVE, THREA ...[more]
- 
- 20 6" X 3,000 LB. MINSTER POWERED STRAIGHTENER / UNCOILER COMBINATION; S/N 13-11111, COMMON BASE, MINSTER CONTROLS (SPEED AND FEED LENGTH), PERFECTO STRAIGHTENER MODEL 18-6-17; S/N S1-86058, CAPACITY .060" AT 3.00" MILD STEEL, .060 AT 6.00" BRASS AND ALUMINUM, (17) STRAIGHTENING ROLLS, VARIABLE SPEED ...[more]

- 21 8" EGAN MODEL X-30-615-1000 CRADLE STRAIGHTENER; S/N 3432, MATERIAL THICKNESS .135 X 12" / .156 X 8", 5-ROLL STRAIGHTENER, 3" DIAMETER ROLLS, 48" OD, POWERED PINCH ROLL, JOG, FORWARD, REVERS, RUN, VARIABLE SPEED, 5 HP; STOCK NO. 17565 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$5 ...[more]
- 
- 22 54" REGAL MODEL 330-SS-54-116 POWERED STRAIGHTENER; S/N 048651162783RI, 54" MAX WIDTH, .018 TO .042 MATERIAL THICKNESS, ROLLS 2 OVER 3, VARIABLE SPEED DRIVE, HARD CHROME ROLLS 3" DIAMETER, 0-100 FPM, POWERED PINCH ROLLS IN AND OUT (1986); STOCK NO. 17251 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT ...[more]
- 
- 23 18" LITTELL MODEL 318 CONTINUOUS STRAIGHTENING FEEDER; S/N 85469-2, CAPACITY 18" WIDTH, MATERIAL THICKNESS .018", SPEED 240-1,400 IPM, HAND AUTO AND INCH, LOOP CONTROLS; STOCK NO. 18042 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$50.00 FOR SIMPLE LIFT & LOAD \*\*
- 
- 24 6,000 LB. LITTELL MODEL 60-24 NON-MOTORIZED UNCOILER; S/N 5-7784-79, CAPACITY 6,000 LB. MANDREL LENGTH 30", MAX COIL OD 60", COIL ID RANGE 16-20", ELECTRIC BRAKE, (4) LEAF MANDREL, MANUAL EXPANSION, OVERALL SIZE APPROX. 63" LEFT TO RIGHT X 40" FRONT TO BACK X 55" HIGH, WEIGHT APPROX. 2,500 LB; STOC ...[more]
- 
- 25 5,000 LB. RAPID AIR MODEL DMP 50 PALLET DECOILER; S/N 93935, 50" MAX COIL OD, 30" MAX COIL HEIGHT, .050 MATERIAL, GOOD CONDITION, 1 HP 115 VOLT; STOCK NO. 17624 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$50.00 FOR SIMPLE LIFT & LOAD \*\*
- 
- 26 4,000 LB. AMERICAN STEEL LINE POWERED UNCOILER; CAPACITY 4,000 LB., MANDREL LENGTH 36", MAX COIL OD 60", COIL ID RANGE 16-21", (3) KEEPERS, OVERARM LIMIT SWITCH, OVERALL SIZE APPROX. 76" LEFT TO RIGHT X 48" FRONT TO BACK X 66" HIGH, WEIGHT APPROX. 3,500 LB; STOCK NO. 18036 \*\* NASHVILLE, TENNESSEE \* ...[more]
- 
- 27 DELETE
- 
- 28 BRADBURY 16-STAND ROLL FORM LINE; S/N 23891, BRADBURY RAFTED 1-1/2" ROLL FORMER, 16-PASSES (COMPLETE EXTRA SET OF RAFTS), 18" ROLLSpace, 4 TO 5-1/2" VERTICAL ADJSUTMENT, CHAIN DRIVE (DRIVEN WITH 2 GEAR BOXES - 1 FOR EACH SET OF 8-STANDS), ADJUSTABLE TRAVERSING BASE WITH 2-POSITIONS, 1,750 RMP, 7.5 ...[more]
- 
- 29 BRADBURY PANEL MILL 14-STAND ROLL FORM LINE; S/N N/A, SHAFTS 3-1/2", ROL SPACE 48", HORIZONTAL SPACE 20", SPEED 200 FPM, CENTER DRIVE MACHINE, CENTER STANDS 28" SPACE, ASC HUMP / BRAKE-SHEAR, 25 HP, 10,000 LB. POWERED UNCOIL, WIDTH OF COIL 48", ID RANGE 18"-22", HYDRAULIC EXPANSION, COIL CAR; STOCK ...[more]
- 
- 30 LOCKFORMER 14-STAND ROLL FROM LINE; S/N N/A, NUMBER OF STANDS (14), NUMBER OF PASSES (10), ROL SPACE 12", SHAFT SIZE 1.5", VERTICAL CENTERS 4", VERTICAL ADJUSTMENT .5", HORIZONTAL CENTERS 6", TOOLING PROFILE / ROLL UP GARAGE DOOR, GEAR DRIVEN, UNIST LUBE SYSTEM, MOTOR 7.5 HP, ELECTRICAL 480 VOLT / ...[more]
- 
- 31 YODER MODEL M3 TUBE MILL; S/N 39774 68259-1, 9-STAND 7-DRIVEN FORMING STANDS, (2) SIZING STANDS, 3" SHAFT, 24" HORIZONTAL CENTERS, 18" ROLL SPACE, JOG CONTROL, BEAD FLASHER / SCARFER, FLYING CUT-OFF ABRASIVE WHEEL, TOOLING 1-5/8", 3-1/2", 2-3/8", 2-7/8", « TURKS HEAD, 40 HP DC VARIABLE SPEED DRIVE, ...[more]
- 
- 32 YODER MODEL M2.5 TUBE MILL; S/N C0-1424, 9-STAND 4-BREADKDOWN STANDS, (3) FINISHING STANDS, (2) SIZING STANDS, 2.5" SHAFTS, HORIZONTAL CENTERS 18", ROLL SPACE 18", « TURKS HEAD, DOUBLE END DRIVE, BEAD FLASHER / SCARFER, JOG PENDANT, TOOLING, TIG WELDER, POWER SUPPLY, MILLER SYNCROWAVE 350, ASL DOUB ...[more]
- 
- 33 WYSONG MODEL 1052 RKB LINE SHEAR; S/N P97-100, 52" WIDTH, AIR CLUTCH, BOW TIE BLADE, 15 HP 230/460 VOLT, 3 HP; STOCK NO. 17515 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$200.00 FOR SIMPLE LIFT & LOAD \*\*
-

- 34 5,000 LB. BRADBURY MODEL 300-24 UNCOILER; S/N 17310, COIL WIDTH 24", MAX OD 60", ID RANGE 15.5" - 21", VARIABLE TENSION DRAG BRAKE, 4-ARM MANDREL, (2) KEEPERS, MANUAL EXPANSION; STOCK NO. 18007 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$100.00 FOR SIMPLE LIFT & LOAD \*\*
- 
- 35 LEE SCHAFFER MODEL 90-1853 COIL END WELDER; S/N 90-1853, MILLER ECONOTWIN HF WELDER, 150 AMP, 8" WIDTH, CART MOUNTED ; STOCK NO. 17325 \*\* NASHVILLE, TENNESSEE \*\* PEARL EQUIPMENT COMPANY HAS QUOTED \$50.00 FOR SIMPLE LIFT & LOAD \*\*
- 
- 36 { Choice of lots: 36, 37 } HASKEL HYDRO SWAGER SYSTEM; S/N 1272139-1, MARK IV POWER SUPPLY 42769, DIGITAL INDICATOR STRAIN GAUGE 3370-S, PUMP DSF-35, INTENSIFIER 42202, MANDREL HOLDER 42203 (2004); STOCK NO. 17454 \*\* NASHVILLE, TENNESSEE \*\*PEARL EQUIPMENT COMPANY HAS QUOTED \$50.00 FOR SIMPLE LIFT ...[more]
- 
- 37 { Choice of lots: 36, 37 } HASKEL HYDRO SWAGE SYSTEM; S/N 57697, MARK IV POWER SUPPLY 42769, DIGITAL INDICATOR STRAIN GAUGE 3370-S, PUMP DSF-35, INTENSIFIER 42202, MANDREL HOLDER 42203 (2004); STOCK NO. 17455 \*\* NASHVILLE, TENNESSEE \*\*PEARL EQUIPMENT COMPANY HAS QUOTED \$50.00 FOR SIMPLE LIFT & LOA ...[more]
- 
- 38 90 TON X 12' CINCINNATI MODEL 90CB10 HYDRAULIC PRESS BRAKE; S/N 41724, OVERALL BEND LENGTH 12'/ 144", DISTANCE BETWEEN HOUSINGS 10'6", STROKE 8", OPEN HEIGHT 15", CLOSED HEIGHT 7", THROAT DEPTH 7", HURCO AUTOBEND 6 CNC BACKGAUGE AND CONTROL, MOTOR 15 HP, OVERALL DIMENSIONS 151" LEFT TO RIGHT X 55" ...[more]
- 
- 39 300 TON X 12' CINCINNATI MODEL SERIES 12 X 10 MECHANICAL PRESS BRAKE; S/N 34447, OVERALL BENDING LENGTH 12', DISTANCE BETWEEN HOUSINGS 10' X 6", STROKE 4", RAM ADJUSTMENT 6", SHUT HEIGHT 12", THROAT DEPTH 10", AIR TRIP MECHANICAL CLUTCH, FLUSH FLOOR DESIGN, MOTOR 15 HP / 480 VOLT / 3 HP, WEIGHT APP ...[more]
- 
- 40 35 TON X 6' WYSONG MODEL 35-72 HYDRA-MECHANICAL PRESS BRAKE; S/N HPB13-180, BED 72", BENDING LENGTH 72", DISTANCE BETWEEN HOUSING 62", STROKE 2-1/2", SPM 42, ADJUSTMENT 3", THROAT 8-1/2", DIE SPACE SDAU 9", AUTOMEC CNC 150 SINGLE AXIS BACK GAUGE, PALM BUTTON / FOOT SWITCH, 5 HP MOTOR, OVERALL SIZE ...[more]
- 
- 41 DELETE
- 
- 42 3/4" X 13' BERTSCH MODEL #14 INITIAL PINCH PLATE ROLL; S/N M-8781, TOP ROLL DIAMETER 16", RATED CAPACITY 13' X \_" MILD STEEL, 4' X 1-3/4" MILD STEEL, MAX ROLL SPACE 13.2", INITIAL PINCH THREE ROLL ARRANGEMENT, AIR DROP END, REAR ROLL ADJUSTMENT WITH DIAL INDICTOR, CONING, DRIVE MOTOR 30 HP, WEIGHT ...[more]
- 
- 43 110 TON GEKA CNC PUNCH; S/N 9702, PUNCHING CAPACITY 110 TONS, CAPACITY IN \_" MATERIAL 1-1/2", CAPACITY IN 1" MATERIAL 1-1/4", THROAT 20, STROKE LENGTH 4", STROKES PER MIN. 42, SPEED MATERIAL POSITIONING 0-936 IPM, TRAVEL 40" X-AXIS, 20" Y-AXIS, EQUIPPED WITH PAXY 1500 CNC XY PLATE POSITIONING AND P ...[more]
- 
- 44 3/8" X 16' PACIFIC MODEL 300G16 HYDRAULIC PLATE SHEAR; S/N S1126, CAPACITY 3/8", MAX CUTTING LENGTH 16', THROAT 18", KNIFE SIZE 1" X 4", BACK GAUGE RANGE 36", NO OF HOLD DOWNS 11, EQUIPPED WITH ADJUSTABLE RAKE ANGLE, FRONT OPERATED POWER BACK GAUGE, FOOT SWITCH, BALL TRANSFERS, ELECTRICAL 460 VOLT ...[more]
- 
- 45 DELETE
- 
- 46 BUTLER NEWELL MODEL ICG100 CNC INTERNAL GRINDER; S/N CNC4069, 2005 RETROFITTED WITH FANUC, HYDRASTATIC HEADSTOCK, (2) 40" 4-JAW CHUCKS, 16" THRU HOLE, 24' BAR FEEDER, 80" TRAVEL ON Z-AXIS, COOLANT WITH FILTRATION, HYDRAULIC SYSTEM, NO GRINDING SPINDLE CURRENTLY WITH MACHINE; STOCK NO. 17641 \*\* NASH ...[more]
- 
- 47 24" X 96" MATTISON MODEL 900/400 FACEGRINDER COMBO GRINDER; S/N 900-56, CAPACITY 24" X 96", WALKER ELECTROMAGNETIC CHUCK 24" X 96", VERTICAL SPINDLE 28" WHEEL SEGMENTED, HORIZONTAL SPINDLE 36" WHEEL SEGMENTED, TABLE 158" X 28", VERTICAL SPINDLE TRAVEL 16" MAX, HORIZONTAL SPINDLE TRAVEL 12" MAX, ENC ...[more]

49 50" X 242" VDF WOHLBERG MODEL U1270S SLIDING HEADSTOCK CNC FLAT BED LATHE; S/N D4175, SWING OVER BED 50", MAX SWING IN GAP 100" X 40" LONG, SWING OVER CROSS SLIDE 35", MAX DISTANCE BETWEEN CENTERS 282", SPINDLE HOLE 4.09", SPINDLE NOSE D1-11 CAMLOCK, SPINDLE SPEED 2.24 TO 450 RPM, TURRET (8) STAT ...[more]

---

50 33" X 196" TOS MODEL SUS80 ENGINE LATHE; S/N 0440845, SWING OVER BED 33", SWIG OVER CROSS SLIDE 20", DISTANCE BETWEEN CENTERS 196", SPINDLE HOLE 3-5/8", MAX WORK CAPACITY 13,227 LB. (2) STEADY RESTS 21" MAX DIAMETER, D-1-6 CAMLOCK SPINDLE NOSE, ENGLISH AND METRIC THREADING, RAPID TRAVERSE, 4-WAY TO ...[more]

---

51 78" TOSHIBA SHIBAURA MODEL TSN20A CNC VERTICAL TURRET LATHE; S/N 112637, CAPACITY SWING 98.4", CHUCK DIAMETER 78.7", RPM 2-125, MAX WORK HIGHT 63", 4-JAW CHUCK (NO JAWS), TABLE LOAD CAPACITY 35,200 LB. TURRET 4-POSITION, HIGH COLUM MACHINE, CONTROL GE FANUC SERIES 18T, VERTICAL TRAVEL OF RAIL HEAD ...[more]

---

52 MART MODEL TORNADO 40 PARS WASHER; S/N 4272, TABLE DIAMETER 41", MAX WORK HEIGHT 63", TABLE CAPACITY 2,000 LB., TOTAL SYSTEM FLOW 221 GPM, FLOW PER NOZZLE 13.8 GPM, SYSTEM PRESSURE 112 PSI, BLAST VELOCITY 129 FT. / SEC., CAPACITY (GAL) 180, GAS HEAT 180,000 BTU, OPERATING TEMP 140-180 DEGREES F., I ...[more]

---

53 GOFF MODEL HP-1316 SPINNING HANGER PARTS WASHER; S/N 92521-50-3643, CAPACITY 13" DIAMETER X 16" HIGH, UP TO 100 LB. PARTS, 3 CHAMBERS, 100 GALLON INTERNAL INSULATED RESERVOIR, TWO EACH 5 HP WATER WHEELS, OIL SKIMMER, -" STEEL CABINET, ONLY 32 HOURS USAGE ; STOCK NO. 17466 \*\* NASHVILLE, TENNESSEE \*\* ...[more]

---